

Rotation code.

* We saw that diversity L can be achieved using a repetition code. However, only one BPSK symbol was sent in $2 \binom{L}{\text{in}} \text{symbol intervals}$.


* We can send 2 bits in 2 symbols using QPSK, by doing the same repetition in both real & imaginary parts.

* How can we send 2 bits in 1 symbol and still have diversity 2?
Using a 16-symbol constellation and repeating it twice.

i.e. 4-PAM in each dimension.



$$\text{Av. energy} = \frac{20b^2}{4} = 5b^2$$



$$\text{Av. energy} = 2b^2$$

For same energy per bit, d_{min} reduces by a factor of $\sqrt{5}$.

* Using the rotation code, we can transmit 2 bits/symbol and still get diversity 2.

We will see what to do in each dimension, i.e., 2 bits over $L=2$ transmissions. (Overall, we have 4 bits in 2 transmissions).

* Consider $u_1 = \pm a$ & $u_2 = \pm a$.


Over the 2 symbol intervals, transmit $\underline{x} = \begin{pmatrix} x_1 \\ x_2 \end{pmatrix}$

given by $\underline{x} = R \begin{pmatrix} u_1 \\ u_2 \end{pmatrix}$ where $R = \begin{pmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{pmatrix}$


the rotation matrix.

4 possible length-2 codewords over 2 intervals are:

$$\underline{x}_A = R \begin{pmatrix} a \\ a \end{pmatrix}, \quad \underline{x}_B = R \begin{pmatrix} -a \\ a \end{pmatrix}, \quad \underline{x}_C = R \begin{pmatrix} -a \\ -a \end{pmatrix}, \quad \underline{x}_D = R \begin{pmatrix} a \\ -a \end{pmatrix}$$



If we use repetition, we use 4-PAM for same rate



This does not use the available degrees of freedom.

Error probability for rotation code:

$$P_r(\text{error}) = P_r(\text{error} | \underline{x}_A \text{ is transmitted})$$

$$= P_r(\underline{x}_A \rightarrow \underline{x}_B) + P_r(\underline{x}_A \rightarrow \underline{x}_C) + P_r(\underline{x}_A \rightarrow \underline{x}_D)$$

Prob. of decoding \underline{x}_B when \underline{x}_A is transmitted.

$$\leq P(\underline{x}_A \rightarrow \underline{x}_B) + P(\underline{x}_A \rightarrow \underline{x}_C) + P(\underline{x}_A \rightarrow \underline{x}_D)$$

Prob. of decoding \underline{x}_B given a constellation with only 2 symbols \underline{x}_A & \underline{x}_B when \underline{x}_A is transmitted

Let h_1, h_2 be the channel fades during intervals 1 and 2.

$$P_r(\underline{x}_A \rightarrow \underline{x}_B | h_1, h_2) = Q \left(\frac{d_{A,B}}{2 \sqrt{N_0/2}} \right)$$

$$= Q \left(\frac{\left\| \begin{pmatrix} h_1 x_{A1} \\ h_2 x_{A2} \end{pmatrix} - \begin{pmatrix} h_1 x_{B1} \\ h_2 x_{B2} \end{pmatrix} \right\|}{2 \sqrt{N_0/2}} \right)$$

$$\left(\text{SNR} = \frac{a^2}{N_0} \right)$$

$$= Q \left(\sqrt{\frac{\text{SNR} (|h_1|^2 |d_1|^2 + |h_2|^2 |d_2|^2)}{2}} \right)$$

$$P(x_A \rightarrow x_B | h_1, h_2) \leq Q \left(\sqrt{\frac{\text{SNR} (|h_1|^2 |d_1|^2 + |h_2|^2 |d_2|^2)}{2}} \right)$$

$$\left(Q(x) \leq e^{-x^2/2} \right) \leq \exp \left(\frac{-\text{SNR} (|h_1|^2 |d_1|^2 + |h_2|^2 |d_2|^2)}{4} \right)$$

Averaging with respect to h_1 and h_2 under the Rayleigh-fading model

$$P(x_A \rightarrow x_B) \leq E_{h_1, h_2} \left[\exp \left(\frac{-\text{SNR} (|h_1|^2 |d_1|^2 + |h_2|^2 |d_2|^2)}{4} \right) \right]$$

$$= E_{h_1} \left[\exp \left(\frac{-\text{SNR} |h_1|^2 |d_1|^2}{4} \right) \right] E_{h_2} \left[\exp \left(\frac{-\text{SNR} |h_2|^2 |d_2|^2}{4} \right) \right]$$

$$\left[\begin{aligned} X_i \triangleq |h_i|^2 \sim \text{exponential } f_{X_i}(x) = e^{-x} \\ E[e^{sX}] = \frac{1}{1-s} \text{ for } s < 1. \end{aligned} \right]$$

$$= \left[\frac{1}{1 + (\text{SNR} |d_1|^2 / 4)} \right] \left[\frac{1}{1 + (\text{SNR} |d_2|^2 / 4)} \right]$$

At high SNR,

$$P(x_A \rightarrow x_B) \leq \frac{1/6}{|d_1 d_2|^2} \text{SNR}^{-2}$$

Let $S_{AB} \triangleq |d_1 d_2|^2$ Squared product distance ^{between x_A & x_B} when average energy ^{is normalized} to 1 per symbol time
 (Product of the distance along each coordinate)²

Similarly, we can bound $P(x_A \rightarrow x_C)$ & $P(x_A \rightarrow x_D)$.

Therefore,

$$P_e(\text{error}) \leq 16 \left(\frac{1}{\delta_{AB}} + \frac{1}{\delta_{AC}} + \frac{1}{\delta_{AD}} \right) \text{SNR}^{-2}$$

$$\leq \frac{48}{\min_{j=B,C,D} \delta_{Aj}} \text{SNR}^{-2}$$

will determine coding gain

Therefore, as long as $\delta_{ij} > 0$ for all i, j , we get a diversity gain of 2.

$\min_{i,j} \delta_{Aj}$ determines performance \rightarrow larger min. product distance implies more coding gain.

* Tightness of upper bound at high SNR (See problem 3.7).

* The rotation angle can be chosen to maximize coding gain. ($\theta^* = \frac{1}{2} \tan^{-1}(2)$, $\min \delta_{ij} = \frac{16}{5}$) (exercise)

Lecture 13: 26/8/2008

* Interpretation on why product distance is important

x_A is confused with x_B if sq. Euclidean distance

$|h_1|^2 |d_1|^2 + |h_2|^2 |d_2|^2$ is of the order of $\frac{1}{\text{SNR}}$.

This happens when both $|h_1|^2 |d_1|^2$ and $|h_2|^2 |d_2|^2$

are of the order of $\frac{1}{\text{SNR}}$. This happens with

probability

$$\left(\frac{1}{|d_1|^2 \text{SNR}} \right) \left(\frac{1}{|d_2|^2 \text{SNR}} \right) = \frac{1}{|d_1|^2 |d_2|^2} \text{SNR}^{-2}$$

* Coding gain over repetition code ≈ 3.5 dB (factor of $\sqrt{5}$ in d_{min}) (exercise)

* Rotation code has better product distance than the repetition code.

The codewords are packed in a 2-D space rather than on a 1-D line as in the repetition code. => Better use of the available degrees of freedom

Generalization to any time diversity code:

Let $\underline{x}_1, \dots, \underline{x}_M$ be the codewords of a time diversity code over L transmissions (block length L).
 \swarrow $L \times 1$ vectors

(Ideal i.i.d channel model) $y_l = h_l x_l + w_l$ for $l = 1, 2, \dots, L$
 $h_l \sim \text{i.i.d. CN}(0, 1)$

$$\frac{1}{ML} \sum_{i=1}^M \|\underline{x}_i\|^2 = 1 \quad \text{(Power constraint Normalization)}$$

$$P_e \leq \frac{1}{M} \sum_{i \neq j} P(\underline{x}_i \rightarrow \underline{x}_j) \quad \text{(Symmetry assumption?)}$$

$$P(\underline{x}_i \rightarrow \underline{x}_j) \leq \prod_{l=1}^L \frac{1}{1 + (\text{SNR} |x_{il} - x_{jl}|^2 / 4)}$$

where x_{il} is the l^{th} component of \underline{x}_i , $\text{SNR} = \frac{1}{N_0}$.

Let L_{ij} be the number of components on which codewords \underline{x}_i & \underline{x}_j differ. Diversity gain of the code is

$$\min_{i \neq j} L_{ij}$$

If $L_{ij} = L$ for all $i \neq j$, then the code achieves full diversity \triangle

$$P_e \leq \frac{4^L}{M} \sum_{i \neq j} \frac{1}{\delta_{ij}} \text{SNR}^{-L} \leq \frac{4^L (M-1)}{\min_{i \neq j} \delta_{ij}} \text{SNR}^{-L}$$

where $\delta_{ij} = \prod_{l=1}^L |x_{il} - x_{jl}|^2$ (Squared product distance between x_i & x_j)

* Binary linear block code + ideal interleaving


\Rightarrow Diversity gain = Minimum Hamming Distance
(Minimum weight)

Binary convolutional code \Rightarrow Diversity gain = Free distance.

Recap: - Time diversity using coding + interleaving

- Decoding delay

- PDF of $\|B\|^2$ for diff. values of L



\leftarrow (Plot this as an exercise)

(See Fig 3.7 in the book
(p63))